


# **Disc Sander**

125 mm (5") MODEL GV5000



003425



## INSTRUCTION MANUAL

#### **WARNING:**

For your personal safety, READ and UNDERSTAND before using. SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE.

# **SPECIFICATIONS**

Model	GV5000
Abrasive disc diameter	125 mm (5")
No load speed (RPM)	4,500/min.
Overall length	180 mm (7 - 1/8")
Net weight	2.2 kg (2.6 lbs)

- Manufacturer reserves the right to change specifications without notice.
- · Specifications may differ from country to country.

# **GENERAL SAFETY RULES**

USA002-2

(For All Tools)

## **∆** WARNING:

**Read and understand all instructions.** Failure to follow all instructions listed below, may result in electric shock, fire and/or serious personal injury.

# SAVE THESE INSTRUCTIONS

#### Work Area

- 1. Keep your work area clean and well lit. Cluttered benches and dark areas invite accidents.
- Do not operate power tools in explosive atmospheres, such as in the presence of flammable liquids, gases, or dust. Power tools create sparks which may ignite the dust or fumes.
- 3. Keep bystanders, children, and visitors away while operating a power tool. Distractions can cause you to lose control.

#### **Electrical Safety**

- 4. Double insulated tools are equipped with a polarized plug (one blade is wider than the other.) This plug will fit in a polarized outlet only one way. If the plug does not fit fully in the outlet, reverse the plug. If it still does not fit, contact a qualified electrician to install a polarized outlet. Do not change the plug in any way. Double insulation I eliminates the need for the three wire grounded power cord and grounded power supply system.
- Avoid body contact with grounded surfaces such as pipes, radiators, ranges and refrigerators. There is an increased risk of electric shock if your body is grounded.

- 6. Do not expose power tools to rain or wet conditions. Water entering a power tool will increase the risk of electric shock.
- 7. Do not abuse the cord. Never use the cord to carry the tools or pull the plug from an outlet. Keep cord away from heat, oil, sharp edges or moving parts. Replace damaged cords immediately. Damaged cords increase the risk of electric shock.
- When operating a power tool outside, use an outdoor extension cord marked "W-A" or "W". These cords are rated for outdoor use and reduce the risk of electric shock.

#### **Personal Safety**

- 9. Stay alert, watch what you are doing and use common sense when operating a power tool. Do not use tool while tired or under the influence of drugs, alcohol, or medication. A moment of inattention while operating power tools may result in serious personal injury.
- 10. Dress properly. Do not wear loose clothing or jewelry. Contain long hair. Keep your hair, clothing, and gloves away from moving parts. Loose clothes, jewelry, or long hair can be caught in moving parts.
- 11. Avoid accidental starting. Be sure switch is off before plugging in. Carrying tools with your finger on the switch or plugging in tools that have the switch on invites accidents.
- 12. Remove adjusting keys or wrenches before turning the tool on. A wrench or a key that is left attached to a rotating part of the tool may result in personal injury.
- 13. Do not overreach. Keep proper footing and balance at all times. Proper footing and balance enables better control of the tool in unexpected situations.
- 14. Use safety equipment. Always wear eye protection. Dust mask, non-skid safety shoes, hard hat, or hearing protection must be used for appropriate conditions. Ordinary eye or sun glasses are NOT eye protection.

#### **Tool Use and Care**

- 15. Use clamps or other practical way to secure and support the workpiece to a stable platform. Holding the work by hand or against your body is unstable and may lead to loss of control.
- 16. Do not force tool. Use the correct tool for your application. The correct tool will do the job better and safer at the rate for which it is designed.
- 17. Do not use tool if switch does not turn it on or off. Any tool that cannot be controlled with the switch is dangerous and must be repaired.
- 18. Disconnect the plug from the power source before making any adjustments, changing accessories, or storing the tool. Such preventive safety measures reduce the risk of starting the tool accidentally.
- 19. Store idle tools out of reach of children and other untrained persons. Tools are dangerous in the hands of untrained users.
- 20. Maintain tools with care. Keep cutting tools sharp and clean. Properly maintained tools with sharp cutting edges are less likely to bind and are easier to control.
- 21. Check for misalignment or binding of moving parts, breakage of parts, and any other condition that may affect the tools operation. If damaged, have the tool serviced before using. Many accidents are caused by poorly maintained tools.
- 22. Use only accessories that are recommended by the manufacturer for your model. Accessories that may be suitable for one tool, may become hazardous when used on another tool.

#### SERVICE

23. Tool service must be performed only by qualified repair personnel. Service or maintenance performed by unqualified personnel could result in a risk of injury.

# 24. When servicing a tool, use only identical replacement parts. Follow instructions in the Maintenance section of this manual.

Use of unauthorized parts or failure to follow Maintenance instructions may create a risk of electric shock or injury.

**USE PROPER EXTENSION CORD:** Make sure your extension cord is in good condition. When using an extension cord, be sure to use one heavy enough to carry the current your product will draw. An undersized cord will cause a drop in line voltage resulting in loss of power and overheating. Table 1 shows the correct size to use depending on cord length and nameplate ampere rating. If in doubt, use the next heavier gage. The smaller the gage number, the heavier the cord.

Ampere Rating		Volts	Total length of cord in feet							
		120 V	25 ft.	50 ft.	100 ft.	150 ft.				
More Than	Not More Than	AWG								
0	6		18	16	16	14				
6	10		18	16	14	12				
10	12		16	16	14	12				
12	16		14 12 Not Recommended							

#### Table 1: Minimum gage for cord

# SPECIFIC SAFETY RULES

USB046-3

DO NOT let comfort or familiarity with product (gained from repeated use) replace strict adherence to sander safety rules. If you use this tool unsafely or incorrectly, you can suffer serious personal injury.

- 1. Accessories must be rated for at least the speed recommended on the tool warning label. Wheels and other accessories running over rated speed can fly apart and cause injury.
- 2. Hold tool by insulated gripping surfaces when performing an operation where the cutting tool may contact hidden wiring or its own cord. Contact with a "live" wire will make exposed metal parts of the tool "live" and shock the operator.
- 3. Always use safety glasses or goggles. Ordinary eye or sun glasses are NOT safety glasses.

- Check the backing pad carefully for cracks, damage or deformity before operation. Replace cracked, damaged or deformed pad immediately.
- NEVER use tool with wood cutting blades or other sawblades. Such blades when used on a sander frequently kick and cause loss of control leading to personal injury.
- 6. Hold the tool firmly.
- 7. Keep hands away from rotating parts.

- 8. Make sure the abrasive disc is not contacting the workpiece before the switch is turned on.
- 9. When sanding metal surfaces, watch out for flying sparks. Hold the tool so that sparks fly away from you and other persons or flammable materials.
- 10. Do not leave the tool running. Operate the tool only when hand-held.
- 11. Do not touch the workpiece immediately after operation; it may be extremely hot and could burn your skin.


- 12. Check that the workpiece is properly supported.
- 13. Pay attention that the wheel continues to rotate after the tool is switched off.
- 14. This tool has not been waterproofed, so do not use water on the workpiece surface.
- 15. Ventilate your work area adequately when you perform sanding operations.
- 16. Use of this tool to sand some products, paints and wood could expose user to dust containing hazardous substances. Use appropriate respiratory protection.

# SAVE THESE INSTRUCTIONS

## **∆** WARNING:

MISUSE or failure to follow the safety rules stated in this instruction manual may cause serious personal injury.

# FUNCTIONAL DESCRIPTION



1. Switch trigger

2. Lock button

### **△** CAUTION:

• Always be sure that the tool is switched off and unplugged before adjusting or checking function on the tool.

### Switch action

### **△** CAUTION:


- Before plugging in the tool, always check to see that the switch trigger actuates properly and returns to the "OFF" position when released.
- Switch can be locked in "ON" position for ease of operator comfort during extended use. Apply caution when locking tool in "ON" position and maintain firm grasp on tool.

To start the tool, simply pull the switch trigger. Release the switch trigger to stop.

For continuous operation, pull the switch trigger and then push in the lock button.

To stop the tool from the locked position, pull the switch trigger fully, then release it.

# ASSEMBLY



#### 1. Side grip

### **△** CAUTION:


• Always be sure that the tool is switched off and unplugged before carrying out any work on the tool.

## Installing side grip (auxiliary handle)


### **△** CAUTION:

• Always be sure that the side grip is installed securely before operation.


Screw the side grip on the tool securely.



- 1. Hex wrench
- 2. Clamp screw
- 3. Countersunk washer
- 4. Abrasive disc
- 5. Plastic pad
- 6. Spindle



# OPERATION



## Installing or removing abrasive disc

Mount the pad onto the spindle. Fit the abrasive disc and countersunk washer on the pad and screw the clamp screw clockwise into the spindle.

To tighten the clamp screw, grip the edge of the pad with your hand, then tighten the screw clockwise with a hex wrench securely.

To remove the disc, follow the installation procedure in reverse.

## Sanding operation

## ▲ CAUTION:

- Always wear safety goggles or a face shield during operation.
- Never run the tool without the abrasive disc. You may seriously damage the pad.

Hold the tool firmly. Turn the tool on and then apply the abrasive disc to the workpiece.

In general, keep the abrasive disc at an angle of about 15 degrees to the workpiece surface. Apply slight pressure only. Excessive pressure will result in poor performance and premature wear to abrasive disc.

# MAINTENANCE

### **△** CAUTION:

 Always be sure that the tool is switched off and unplugged before attempting to perform inspection or maintenance.

To maintain product SAFETY and RELIABILITY, repairs, carbon brush inspection and replacement, any other maintenance or adjustment should be performed by Makita Authorized or Factory Service Centers, always using Makita replacement parts.

# ACCESSORIES

### **△** CAUTION:

 These accessories or attachments are recommended for use with your Makita tool specified in this manual. The use of any other accessories or attachments might present a risk of injury to persons. Only use accessory or attachment for its stated purpose.

If you need any assistance for more details regarding these accessories, ask your local Makita service center.

- Plastic pad
- Abrasive discs
- Wrench 5
- Grip 36

First-Class Postage Required

Post Office will not deliver without proper postage.

Makita U.S.A., Inc. 14930 Northam Street La Mirada, CA 90638-5753

I.

Cont

Fold

Ռեսհավհանհետհետհետհետ

# MAIL THIS PORTION

# Your answers to the following questions are appreciated.

					Ŭ	•				•••					
. This product was p	urchase	d from:	:			3.	How d	id you le	earn ab	out thi	s prod	uct:			
Home Center		C	Other (		)		Maga	azine			F	ladio			
Hardware/Lumber	Store						From	Dealer			E	xhibition			
Tool Distributor							News	spaper			F	rom Frie	nd		
Industrial Supply							Store	e Display	'		P	revious	Usage		
Construction Supp	oly						Cata	log			C	Other (		)	
Use of the product	is inten	ded for:	:			4.	Most fa	avored	points a	are:					
Construction Trade	uction Trade					Design					Repair Service				
Industrial Mainten	ance						Featu	ures				urability			
Home Maintenand	e						Size				- P	ower			
Hobby							Price				C	Other (		)	
Other (	)						Maki	ta Brand	I						
Any comments:															
Any comments.															
DATE PURCHASED						MODE	L NO.								
MONTH	DAY YEAR														
						SERIAL NO.									
											ST	ATUS	SI	EX	
NTL. LAST NAM	E / COM	PANY N	IAME								Marrie	d Single	М	F	
TREET ADRESS															
CITY															
OTATE				-				DUONS							
STATE			P COD	E		1		PHONE	:		1				
AGE:	Under	19	20-	-29		30-39		40-4	9	5	0-60		Over 6	0	
										·					
SUBE TO COME	N FTF T	HE CU	STOM											S	

Please return this portion by facsimile or mail. Facsimile No: (714) 522-8133

Paste

Paste

# FACTORY SERVICE CENTERS

### 1-800-4-MAKITA

# RETAIN THIS PORTION FOR YOUR RECORDS

ALABAMA 2365 Pelham Parkway Pelham, AL 35124 (205) 620-1791

ARIZONA 3707 E. Broadway Rd., Ste. 6 Phoenix, AZ 85040 (602) 437-2850

ARKANSAS Shackleford Shopping Center 240 South Shackleford Rd., Ste. C Little Rock, AR 72211 (501) 224-5733

CALIFORNIA 41850 Christy St. Fremont, CA 94538-5107 (510) 657-9881

1421 N. Clovis Ave., Ste. 112 Fresno, CA 93727 (559) 252-5166

14930 Northam St. La Mirada, CA 90638-5753 (714) 522-8088

1970 Fulton Avenue Sacramento, CA 95825 (916) 482-5197

1440 South "E" Street San Bernardino, CA 92408 (909) 885-1289

7674 Clairemont Mesa Blvd. San Diego, CA 92111 (858) 278-4471

1714 E.McFadden Ave., Unit M Santa Ana, CA 92705 (714) 667-5066

1565 Winchester B. Campbell, CA 95008-0501 (408) 379-0377

16735 Saticoy St., Ste. 105 Van Nuys, CA 91406 (818) 782-2440 COLORADO 11839 E. 51st Ave. Denver, CO 80239-2709 (303) 371-2850

CONNECTICUT 508 Spring St. Windsor Locks, CT 06096 (860) 292-6405

FLORIDA 620 Douglas Ave. Suite 1302 Altamonte Springs, FL 32714 (407) 774-6000

750 East Sample Road Pompano Beach, FL 33064 (954) 781-6333

Thompson Center Waters 5501 W. Waters Ave., Ste. 406 Tampa, FL 33634 (813) 886-8292

GEORGIA 4680 River Green Parkway Duluth, GA 30096-2566 (770) 476-8911

HAWAII 4510 Salt Lake Blvd., Suite A7 Honolulu, HI 96818 (808) 847-0038

ILLINOIS 1450 Feehanville Dr. Mt. Prospect, IL 60056-6011 (847) 297-3100

INDIANA 8403 Michigan Road, Unit 1 Indianapolis, IN 46268 (317) 334-9980

KANSAS 8819 W. 95th St. Overland Park, KS 66212 (913) 642-1111 KENTUCKY 1215 S. Hurstbourne Parkway Louisville, KY 40222 (502) 326-3740

LOUSIANA 5626 Jefferson Hwy. Harahan, LA 70123 (504) 733-4138

MARYLAND 7541 - 45 Ritchie Highway Glen Burnie, MD 21061 (410) 590-0160

MASSACHUSETTS 232 Providence Hwy. Westwood, MA 02090 (617) 461-9754

MICHIGAN 37454 Ann Arbor Trail Livonia, MI 48150 (313) 432-1012

MINNESOTA 6427 Penn Ave. South Richfield, MN 55423 (612) 869-5199

MISSOURI 9876 Watson Road St. Louis, MO 63126-2221 (314) 909-9889

NEBRASKA 4129 S. 84th St. Omaha, NE 68127 (402) 597-2925

NEVADA 3375 S. Decatur Blvd. Suites. 22 - 24 Las Vegas, NV 89102 (702) 368-4277

NEW JERSEY 251 Herrod Blvd. Dayton, NJ 08810-1539 (609) 655-1212 NEW MEXICO 5805 Menaul Blvd. NE Albuquerque, NM 87110 (505) 881-4619

NEW YORK 4917 Genessee Street Cheektowaga, NY 14225 (716) 685-9503

131-35 31st Ave. Flushing, NY 11354 (718) 886-0971

NORTH CAROLINA 3501-G S. Tryon St. Charlotte, NC 28217 (704) 527-0611

OHIO 6253 E. Main St. Columbus, OH 43213 (614) 860-0222

6379 Pearl Road Parma Heights, OH 44130 (440) 843-7555

1617 E. Kemper Rd. Sharonville, OH 45246 (513) 771-0788

OKLAHOMA 552 E. Memorial Road Oklahoma City, OK 73114 (405) 752-2655

OREGON 828 19th Avenue., N.W. Portland, OR 97209 (503) 222-1823

PENNSYLVANIA Springwater Plaza 364 Wilmington W. Chester Pike Glen Mills, PA 19342 (610) 459-4122

6200 Babcock Blvd Pittsburgh, PA 15237 (412) 366-6363 PUERTO RICO 200 Guayama St. Hato Rey, PR 00917 (787) 250-8776

TENNESSEE 4655 Nolensville Rd Nashville, TN 37211 (615) 331-9922

TEXAS 12801 Stemmons Fwy Ste. 809 Farmers Branch, TX 75234 (972) 243-1150

12701 Directors Dr. Stafford, TX 77477-3701 (281) 565-8665

3453 IH-35 North, Ste. 101 San Antonio, TX 78219 (210) 228-0676

UTAH 145 E. 1300 S., Ste. 101 Salt Lake City, UT 84115 (801) 359-3410

VIRGINIA 5760 Northampton Blvd,. Ste. 102 Virginia Beach, VA 23455 (757) 460-0280

WASHINGTON 22220 84th Ave. So., Bldg. A Kent, WA 98032 (253) 395-8055

WISCONSIN Lincoln Plaza Shopping Ctr. 2245 S. 108th St. West Allis, WI 53227 (414) 541-4776

#### CUSTOMER'S RECORD

When you need service: Send complete tool (prepaid) to one of the Makita Factory Service Centers listed, or to an Authorized Makita Service Center. Be sure to attach a letter to the outside of the carton detailing the problem with your tool.

hd Date Purchased Dealer's Name & Address rized re e of Model No. Serial No.

# WARNING

Some dust created by power sanding, sawing, grinding, drilling, and other construction activities contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Some examples of these chemicals are:

- · lead from lead-based paints,
- crystalline silica from bricks and cement and other masonry products, and
- arsenic and chromium from chemically-treated lumber.

Your risk from these exposures varies, depending on how often you do this type of work. To reduce your exposure to these chemicals: work in a well ventilated area, and work with approved safety equipment, such as those dust masks that are specially designed to filter out microscopic particles.

# MAKITA LIMITED ONE YEAR WARRANTY

## Warranty Policy

Every Makita tool is thoroughly inspected and tested before leaving the factory. It is warranted to be free of defects from workmanship and materials for the period of ONE YEAR from the date of original purchase. Should any trouble develop during this one-year period, return the COMPLETE tool, freight prepaid, to one of Makita's Factory or Authorized Service Centers. If inspection shows the trouble is caused by defective workmanship or material, Makita will repair (or at our option, replace) without charge.

This Warranty does not apply where:

- repairs have been made or attempted by others:
- repairs are required because of normal wear and tear:
- the tool has been abused, misused or improperly maintained:
- alterations have been made to the tool.

IN NO EVENT SHALL MAKITA BE LIABLE FOR ANY INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES FROM THE SALE OR USE OF THE PRODUCT. THIS DISCLAIMER APPLIES BOTH DURING AND AFTER THE TERM OF THIS WARRANTY.

MAKITA DISCLAIMS LIABILITY FOR ANY IMPLIED WARRANTIES, INCLUDING IMPLIED WARRANTIES OF "MERCHANTABILITY" AND "FITNESS FOR A SPECIFIC PURPOSE," AFTER THE ONE-YEAR TERM OF THIS WARRANTY.

This Warranty gives you specific legal rights, and you may also have other rights which vary form state to state. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. Some states do not allow limitation on how long an implied warranty lasts, so the above limitation may not apply to you.

# Makita Corporation

3-11-8, Sumiyoshi-cho, Anjo, Aichi 446-8502 Japan